

Subsection 4.30
Removing Treated and Untreated Base and Asphalt Pavement

- I. Scope:** Break, Remove, and store or dispose of existing asphalt pavement, including surface treatments, and treated or untreated base materials. .
- II. Construction:** Break material retained by the City into pieces not larger than 6 inches. Remove existing asphalt pavement before disturbing the stabilized base. Avoid contamination of the asphalt materials and damage to adjacent areas. Repair material damaged by operations outside the designated locations. Stockpile materials designated salvageable at designated sites. Prepare stockpile site by removing vegetation and trash and by providing for proper drainage. Material not designated to be salvaged will become the property of the Contractor. When this material is disposed of, do so in accordance with federal, state, and local regulations.
- III. Measurement:** This Subsection will be measured by the 100-foot station along the baseline of each roadbed or by the square yard of existing treated or untreated base and asphalt pavement in its original position.
- IV. Payment:** The work performed in accordance with this Subsection and measured as provided under “Measurement” will be paid for at the unit price bid for “Removing Treated and Untreated Base and Asphalt Pavement” of the depth specified. This price is full compensation for breaking the material, loading, hauling, unloading, stockpiling or disposing; repair to areas outside designated locations for removal; and equipment, labor, tools, and incidentals.

LAST PAGE OF THIS SUBSECTION